



深圳市齐普光电子有限公司
SHENZHEN CHIP OPTECH CO.,LTD.

PH7.62MM INDOOR SMD 1BY1 FULL COLOR LED DISPLAY

Product model number	PH7.62SIRL4-S132x16
1.Pixel	
Pixel Led	Smd 0805
Pixel Configuration	1R, 1G, 1B
Wave length (nm)	R: 626-628, G: 518-520, B: 466-468,
Pixels Pitch (mm)	7.62
2.Module	
Module Size (mm)	244 * 122 * 20
Module Pixels (dot)	32 * 16
3.Unit box	
Module quantities(pcs/box)	4 (L) * 8 (H)
Unit box size (mm)	976 (L) * 976 (H) * 180
Unit box Pixels (dot)	128 * 128
Unit box material	Aluminum or Iron
Weight (kg/box)	Aluminum : 40 or Iron : 50
4.Packaging	
Packing Way	Two unit boxes packed into one
Packing box material	Wooden case or Flight box
Packing box size (mm)	1100 * 1150 * 480



深圳市齐普光电子有限公司
SHENZHEN CHIP OPTECH CO.,LTD.

5.electricity parameter	
Pixel density (dots/m ²)	17220
White Balance Brightness(cd/m ²)	≥800
Color temperature(K)	5000—9500 (choice by user)
Brightness Adjusted	100 grade by software, or by Auto-optic induced.
View Angel	Horizontal 140°; Vertical 140°
Best viewing distance(m)	≥5
Communication distance(m)	Internet Wire: 120 Fiber Cable: 1000
Screen work Method	Scan: 1/4
LED driving method	Constant driving current
Gray Grades	16384 levels for each color
Display Color	4, 398, 046, 511, 104
Refresh Frequency (Hz)	≥180
Picture display method	Dots to dots display synchronized with CRT
Signal interface	DVI
Input signal	Video: PAL/NTSC optioned. VGA, Svideo, DVD, TV
Display format	800 * 600, 1024 * 768, 1280*1024
Software	Support windows series system
Protection grades	IP64
Working temperature(°C)	-10~+50



深圳市齐普光电子有限公司
SHENZHEN CHIP OPTECH CO.,LTD.

Humidity(RH)	Up to 95
Stored temperature (°C)	-30~+70
Screen Lifetime(hours)	≥100,000
Out of controlled dots	≤3/10,000 (Out of controlled dots means the pixels of which the brightness and the wave length are both >10% depart to the normal one)
Whole display flatnes	Less than 1mm Juncture
Maintance way	Back-maintained or front-maintained, modules displaced
Switch power supply	Single Phase AC: 110V/60Hz or 220V/50Hz
Power Consumption (w/m ²)	Max: 2200, Average: ≥ 1000